



AD5050A – High Resin – FAR FOIL

AD5050A – High Resin – FAR FOIL

TTR Properties

| | |
|---------------------|--------------|
| Base Film Thickness | 5.7 ± 1.0μ |
| Total Thickness | 8.0 ± 1.0μ |
| Ink Color | Black |
| Ink Melting Point | 105°C |
| Max. Print Speed | 75 mm/second |

Resistance

| | |
|----------|-----------|
| Scratch | Excellent |
| Chemical | Good |
| Alcohol | Average |
| Heat | Excellent |
| Water | Good |

Recommended Substrates

| | |
|-----------------------|-----------------------------|
| Synthetics | Polypropylene & Polyester |
| Coated Textile Labels | Arrow Fabritag FAR Material |

Storage: 5° to 35°C; 30 to 85% RH; Shelf Life 1 Year

Recommended Applications



- Garment Care Labels
- Textiles
- Preprinted Tag & Label Stocks
- Circuit Boards
- Chemical Drums
- Electronic Components
- Product ID Labels
- Print & Apply Applications
- Asset Tracking
- Pharmaceutical, Medical & Healthcare
- Outdoor
- Industrial Applications
- Heat Shrink Wrap
- Automotive

Certifications

- RoHS (2002/95/EC)
- UL Listed
- FDA Listed
- BS5609 Compliant

Withstands washing, dry cleaning and ironing.
Provides Halogen-type solvent resistance.
Withstands autoclaving.

